

- 8CH analog video input, compatible • with 5MP/4MP/1080p/720p AHD camera and CVBS input
- 4CH IPC input, compatible with 5MP • /4MP/3MP/1080p/720p camera
- 1 SATA HDD, up to 8TB per HDD ٠
- H.265 / H.264 compression •
- Video management with sureSIGHT •
- Supporting sureLINK for dynamic **IP** Internet connection
- iView HD for remote monitoring • on mobile phones

Unit: mm		
	300 mm	
		0 45 mm 2.1 mm
<u> </u>	248.4 mm	
O	••••••••••••••••••••••••••••••••••••••	
		,

				Normal:
Terms & Conditions 使用細則 Design and specifications are subject to change without prior notice. Copyright © 2018 Signal Communications Limited. TeleEye is a trademark of Signal Communications Limited and is registered in China, European Community, Hong Kong, U.S. and other countries. All other trademarks are the property of their respective owners.	RECORDING		Max. RECORDING PERFORMANCE	1080P@12fps(PAL) / 15fps (NTSC)
				720P@25fps (PAL) / 30fps (NTSC)
				CVBS WD1@25fps (PAL) / 30fps (NTSC)
				Lite mode:
				5MP Lite(1280x1936)@10fps,
				4MP Lite(1280x1440)@12fps(PAL) / 15fps (NTSC),
				1080P Lite(960x1080)@25fps (PAL) / 30fps (NTSC)
			PLAYBACK	8CH playback
				Play, Forward, Backward, Pause, Digital zoom
	COMMUNICATION	Г	NETWORK	RJ45 100Mbps × 1
			CONCURRENT USER	5
			WEB SERVER	Built-in
			RS485	RS485 ×1, connect to PTZ or keyboard
		L	USB	USB2.0 × 2
	EVENT HANDLING POWER	Г	EVENT TYPE	Video motion detection, External alarm, Video loss
			ACTION TYPE	Recording, Snap, Email, Preset
			ALARM INPUT	8
		L	RELAY OUTPUT	2
		Г	VOLTAGE	DC 12V
			POWER SUPPLY	DC12V / 2A
		L	MAX. RATING	≤ 12 W (without HDD)
	OPERATING	Г	AMBIENT TEMPERATURE	-10°C - 50°C
TeleEye Group Hong Kong China Malaysia Philippines South Africa Sri Lanka United Kingdom	ENVIRONMENT	L	RELATIVE HUMIDITY	10% - 90%
	MECHANICAL DESIGN	Г	DIMENSION	300mm (W) x 260mm (D) x 52mm (H)
		L	WEIGHT	1.16kg

JN6508-S 2MP AHD & IP Hybrid DVR

Model

ANALOG CAMERA

NO. OF CHANNEL

NO. OF CHANNEL

IP CAMERA AUDIO INPUT 4

DIGITAL VIDEO

COMPRESSION

IP CAMERA

VGA

BNC

INPUT

MODE

HDD TYPE

OUTPUT

VIDEO INPUT

VIDEO OUTPUT

AUDIO



BNC x 8

RCA x 8

RCA x 1

H.265 / H.264

4

JN6508-S

Compatible with 5MP / 4MP / 3MP / 1080P / 720P IP camera

1 channel 1920x1080 / 1280x1024 / 1024x768

1 channel, 1920x1080 / 1280x1024 / 1024x768

CVBS (used as the main or spot output)

Manual, Schedule, Motion, Event-driven

SATA x1 (Max. 8TB per HDD)

Compatible with 5MP / 4MP/ 1080P / 720P AHD camera and CVBS input