



Features



- 1080p IR dome
- 1 / 2.7 " 2MP CMOS Sensor, 25/30fps
- Enhanced H.264 / MJPEG compression
- 3 independent video streams
- f=3.6mm fixed iris lens
- ~15m IR illumination range
- IP66 & IK10 ingress protection
- Power over Ethernet, PoE
- True day & night operation with auto IR-cut filter
- ONVIF Profile S

Specifications

MODEL		MP2121E-HD
VIDEO	IMAGE SENSOR	1 / 2.7 " 2MP CMOS Sensor
	RESOLUTION	1080P (1920×1080), 720P (1280×720), D1, CIF, 480×240
	FRAME RATE	Up to 25/30fps
	MINIMUM ILLUMINATION	0.05 lux @F1.2,AGC ON; 0 lux with IR ~15m
	LENS	f=3.6mm Fixed Iris Lens, angle of view: 77°
	AUTO IR-CUT FILTER	Yes
	VIDEO SETTINGS	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR
AUDIO	INPUT	1 ch
CONNECTIVITY	NETWORK INTERFACE	RJ-45
	NETWORK PROTOCOL	TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	DYNAMIC IP	sureLINK, DDNS
	VIDEO MAIN STREAM RESOLUTION	1920 x 1080 / 1280 x 720
	VIDEO SUB STREAM 1 RESOLUTION	D1 / CIF
	VIDEO SUB STREAM 2 RESOLUTION	480 x 240 / CIF
	CONCURRENT USERS	4 (Independent)
COMPRESSION	WEB SERVER	Built-in
	VIDEO COMPRESSION	Enhanced H.264 / MJPEG
	VIDEO STREAMING	3 Independent Streams
POWER	POWER IN	12V DC / PoE
	MAX. RATING	3.5W / 4W (IR On)
OPERATING ENVIRONMENT	AMBIENT TEMPERATURE	-20°C - 50°C
	RELATIVE HUMIDITY	10 ~ 90% (No Condensation)
MECHANICAL DESIGN	WEATHER PROOF	IP66
	VANDAL RESISTANT	Yes
	NET WEIGHT	610g

Dimensions

Unit: mm



TeleEye Group
 Hong Kong Bangladesh China Malaysia
 Philippines South Africa Sri Lanka Turkey U.K.

DISTRIBUTED BY:

www.TeleEye.com

Design and specifications are subject to change without prior notice. Copyright © 2016 Signal Communications Limited.
 TeleEye is a trademark of Signal Communications Limited and is registered in China, European Community, Hong Kong,
 U.S. and other countries. All other trademarks are the property of their respective owners.

Printed: 2016.12