



Features

- 1/4" Colour CCD
- Resolution:
500 (Day) / 570 (Night) TVL
- Minimum Illumination 0.02 Lux
- 128 Presets, 1 Patrol
- 100X Zoom; Optical: 10X;
Digital Zoom: 10X
- IP66 weather proof standard



TeleEye RX-KB03

Specifications

| MODEL | Indoor Wall Mount DM462 | Outdoor Wall Mount DM463 |
|-------------------------|---|-----------------------------|
| | CAMERA OPTICS | |
| SCANNING SYSTEM | PAL (625 lines, 50 fields per second) NTSC (525 lines, 60 fields per second) | |
| IMAGE SENSOR | 1/4" interline transfer CCD | |
| RESOLUTION | 500 (Day) / 570 TVL (Night) | |
| MINIMUM ILLUMINATION | 0.02 Lux@F1.8 | |
| VIDEO OUTPUT LEVEL | 1.0Vp-p (75Ω, composite) | |
| VIDEO S/N RATIO | ≥50dB (AGC Off) | |
| WHITE BALANCE | Auto / Manual | |
| GAIN CONTROL | Auto / Manual | |
| ELECTRONIC SHUTTER | 1/50 – 1/120,000 sec | |
| IRIS | Auto / Manual | |
| BACK LIGHT COMPENSATION | On / Off | |
| LENS | Aperture stop: F1.8 ~ 3.2 | |
| | Focal length: f=3.8 ~ 38mm | |
| | Viewing angle: 5.58° ~ 51.2° | |
| ZOOM | Optical: 10X / Electronic: 10X (Total: 100X) | |
| PROTOCOL | TeleEye DM2, Pelco D, Pelco P | |
| | MECHANICAL DESIGN | |
| PANNING | Range: 360° Continuous rotation, Speed: 0.1 ~ 240°/sec | |
| TILTING | Range: 0° ~ 90° Flip, Speed: 0.1 ~ 120°/sec | |
| CONTROL | 128 Preset points, 1 Auto Scan, 6 Programmable Tours | |
| | POWER / ENVIRONMENT | |
| WEATHER PROOF STANDARD | - | IP66 |
| FAN | - | Auto Start |
| HEATER | - | Auto Start |
| OPERATING TEMPERATURE | 0° ~ 50° | -30° ~ 60° |
| POWER SOURCE | AC 24V, 1500mA, 10W | AC 24V, 2000mA, 33W |
| NET WEIGHT (KG) | 1.06 | 1.34 |

Mounting Options

| | | | |
|---------|--|---------|---|
| DM46-CL | Recessed Ceiling Mount Fixture for DM462 | DM46-CN | Corner Mount Bracket for DM462 & DM463 |
| DM46-PL | Pole Mount Bracket for DM462 & DM463 | DM46-PD | Pendant Mount Bracket for DM462 & DM463 |



TeleEye Group
Hong Kong (Head Office)
 Signal Communications Limited

Units 202-3, 2/F, Laford Centre, 838 Lai Chi Kok Road, Kowloon, Hong Kong
 International: (852) 2995 5996
 Fax: (852) 2995 5901
 Hong Kong: (852) 2995 5992
 Email: info@TeleEye.com

China Tel: (86) 755 2671 2122 Email: info@TeleEye.com.cn
Singapore Tel: (65) 6745 3921 Email: sales@TeleEye.com.sg
U.K. Tel: (44) 1628 776061 Email: info@TeleEye.co.uk
Croatia Tel: (385) 52-383102 Email: info@TeleEye.hr

Macau Tel: (853) 28575933 Email: info@TeleEye.com.mo
Philippines Tel: (632) 3650897 Email: contact@TeleEye.com.ph
Mauritius Tel: (230) 686 5238 Email: info@TeleEye.com.mu
South Africa Tel: (27) 11 557 9200 Email: info@TeleEye.co.za