Feature-packed DVR with User-friendly Operation

TeleEye

0

×

RW

TeleEye RA Series is a range of feature-rich and user-friendly 4-, 8- and 16-channel digital video recorders providing high quality video recording and playback. Incorporating with advanced proprietary SMAC compression technology, TeleEye RA can provide 60% longer recording time than other MPEG-4 DVRs.

TeleEye RA offers multiple recording modes and full control of recording rate and picture quality, easy search and efficient playback capabilities. Its built-in VGA interface allows the use of low cost flat screen displays while its USB interface and built-in DVD writer enable fast video extraction for evidential purposes. Its hard disk health check function can anticipate hard disk failure and notify users to repair the technical issues.

With its secure functionality and reliable operation at an affordable price, TeleEye RA is your best choice of digital video recorder!



IR Remote Control for RA

TeleEye

RA

TeleEve



Powered by

TeleEye Digital Video Recorder



MODEL		RA204	RA208	RA216	RA304	RA308	RA316	
INPUT STANDARD			PAL/NTSC; composite video, 1 Vp-p, BNC					
INPUT CHANNELS		4	8	16	4	8	16	
OUTPUT	VGA							
	Composite		PAL/NTSC; composite video, 1 Vp-p, BNC					
	Channels		1 VGA, 1 composite					
RECORDING MODE				manual, schedul <mark>e, event, motion</mark>				
HDD - SATA		Interr	nal x 1	Internal x 2		Internal x 1		
MAX. RECORI	MAX. RECORDING RATE		(P) : 25fps at 720 x 576 pixels; 100fps at 360 x 288 pixels					
			(N) : 30					
VIDEO EXTRACTION			network, USB		networ	k, USB, built-in DV	D writer	
NETWORK			RJ-45,	10/100 base-T ethernet (auto-sensing), UPNP		UPNP		
CONCURRENT USERS				2 (indep <mark>endent)</mark>				
WEB SERVER				Buil <mark>t-in</mark>				
TELEMETRY CONTROL			Camera port: RS-422/ <mark>485: 2-way termina</mark> l,					
INTERFACE			asynchronous, 8 data bits, 1 stop bit, no parity, 2.4-19.2kbps					
USB				USB2.0				
AUDIO INPUT				2 channels, R	CA, line level			
AUDIO OUTPUT			Live / Playback: 1 channel, RCA, line level					
EVENT TYPE			alarm, motion, video loss, disk full, hard disk failu		failure			
ACTION TYPE			recording, buzzer, switch					
EXTERNAL AL	ARM INPUTS		4 x NC / NO					
RELAY SWITC	RELAY SWITCH		1 Channel; Push-button / Latch; 24V AC, 1000mA					
POWER		12V D0	C; 30W	12V DC; 60W	12V DC; 50W	12V D0	C; 60W	
OPERATION ENVIRONMENT		Ambient Temp.: 5°C - 40°C; Relative Humidity: <85% (non condensation)						
DIMENSION (W x L x H)mm		230 x 2	42 x 65	320 x 242 x 65		320 x 398 x 65		
WEIGHT		1.7	′kg	2.3kg	4.3	kg	4.4kg	

- Up to 16 video & 4 alarm input models
- Recording up to 100/120fps
- Triplex operation: simultaneous monitoring, recording & playback

- Bult-in web server & accessible through web browser

Recording Size Requirements on TeleEye RA Digital Video Recorders

Model	D1: 72	0 x 576	CIF: 360 x 288		
	Frame Rate: (fps)	Size per day (GB)	Frame Rate (fps)	Size per day (GB)	
RA204 / RA304	25	26	100	30	
RA208 / RA308	25	36	100	40	
RA216 / RA316	25	46	100	50	

Remark: The above calculation is based on PAL video standard and recording of all cameras with moderate motion at medium quality setting. Actual recording size required is subject to actual camera situation.



TeleEye Group

Signal Communications Limited Units 202-203, 2/F, Laford Centre, 838 Lai Chi Kok Road, Kowloon, Hong Kong International: (852) 2995 5996 Hong Kong: (852) 2995 5992 Fax: (852) 2995 5901 Email: info@TeleEye.com Web: www.TeleEye.com

TeleEye Europe Ltd. Tel: (44) 1628 776061 Email: info@TeleEve.co.uk Web: www.TeleEye.co.uk

TeleEye (S) Pte Ltd. TeleEye Hrvatska Tel: (385) 52-383-102 Tel: (65) 6745-3921 Email: sales@TeleEye.com.sg Web: www.TeleEye.com.sg Email: info@TeleEye.hr Web: www.TeleEye.hr

Email: info@TeleEye.co.za Web: www.TeleEye.co.za

TeleEye (South Africa) (Pty) LtdTeleEye Digital TechnologyTel: (27) 11 557 9200(Shenzhen) Co., Ltd. Tel: (86) 755-2671-2122 Email: info@TeleEye.com.cn Wb: www.TeleEye.com.cn

TeleEye (Mauritius) Ltd. Tel: (230) 686 5238 Email: info@TeleEve.com.mu Web: www.TeleEye.com.mu

TeleEye Philippines, Inc. Tel: (63) 2-3650897 Email: contact@TeleEve.com.ph Web: www.TeleEye.com.ph

Companhia TeleEye (Macau) TeleEye Lanka (Pvt) Ltd Limitada Tel: (853) 2857 5933 Email: info@TeleEye.com.mo Web: www.TeleEye.com.mo

Tel: (94) 11-2695652-4 Email: info@TeleEve.com.lk Web: www.TeleEye.com.lk

*Java: Oracle Java 6 or above

*IE: Windows Internet Explorer Version 6 or above

Features and specifications are subject to change without prior notice. Measurement in this leaflet is based on a set of standard videos. Actual recording size and transmission frame rate is subject to actual camera situation. Copyright © 2011 Signal Communications Limited. TeleEye and SMAC-M are trademarks of Signal Communications Limited. TeleEye is registered in China, European Community, Hong Kong, U.S. and other countries. All other trademarks are the property of their respective owners Reprint : 2011.12

PC Requirements

IE browser*				
CPU:	Intel [®] Core™ i3 Processor			
RAM:	2 GB or above			
HDD:	10 GB of free disk or above			
Display:	Direct 3D, Nvidia® GeForce® GT220/			
	ATI® Radeon® HD 5450 or Above			
OS:	MS Windows XP, Vista, 7			