



Features

- 4K (3840 x 2160)
- H.265, Enhanced H.264
- Hacker Resistant
- PoE Support
- Pre / Post Alarm Image
- Arm / Disarm Interface
- E2E Health Check
- RAID 5

Specifications

MODEL		GN8616
CAMERA INTERFACE	CONFIGURATION	Dedicated network / Shared network
	RESOLUTIONS	4K, WQHD, 1080p, 720p
	MAX. CHANNELS	16
	DEDICATED VIDEO PORTS	16x, 100base-T, PoE
	COMPATIBLE MODELS	TeleEye MP, MQ & ONVIF (Profile S)
VIDEO	OUTPUTS	1x HDMI (max. resolution 4K) 1x VGA (max. resolution 1080p)
CODING	VIDEO & AUDIO	Enhanced H.264, H.264, H.265
RECORDING	MODES	Manual, Scheduled, Event-driven
	STORAGE	8 x SATA, internal
	MAX. RECORDING PERFORMANCE	25fps per channel @ 4K 25fps per channel @ WQHD 25fps per channel @ 1080p
	RAID5	Yes
EVENT	TYPES	External Alarm, Video Motion Detection, System Tamper, Power Interruption, HDD Failure
	ACTIONS	Dialback, Buzzer, Email Notification, Relay Control, Telemetry Preset
	CONTROLS	Arm/Disarm, Security Switch, Power Interruption, Tamper Detection
	ALARM INPUTS	4x on DVR / Alarm Inputs on Cameras
	VIDEO MOTION DETECTION	Yes
	PRE/POST ALARM IMAGE SEQUENCE	Yes
AUDIO	INPUTS	1x RCA on DVR / Audio Inputs on Cameras
	OUTPUTS	1x RCA on DVR / Audio Outputs on Cameras
COMMUNICATION	NETWORK	100/1000 based-T
	SURELINK	Yes
	THROUGHPUT CONTROL	Yes
	WEB SERVER	Built-in
	JOYSTICK CONTROL	RX-KB07
	USB	3 x USB 2.0 (1 Front, 2 Rear)
POWER	RATING	AC 100-240V, 3.5-2A
OPERATING ENVIRONMENT	AMBIENT TEMPERATURE	-10°C - 55°C
	RELATIVE HUMIDITY	10% - 90% (no condensation)
MECHANICAL DESIGN	DIMENSION	440x95x440mm
	WEIGHT	7.6kg

DISTRIBUTED BY:

TeleEye Group

Hong Kong China Malaysia
Philippines South Africa Sri Lanka Turkey U.K.

Design and specifications are subject to change without prior notice. Copyright © 2018 Signal Communications Limited. TeleEye is a trademark of Signal Communications Limited and is registered in China, European Community, Hong Kong, U.S. and other countries. All other trademarks are the property of their respective owners.



Features

- 4K (3840 x 2160)
- H.265, Enhanced H.264
- Hacker Resistant
- PoE Support
- Pre / Post Alarm Image
- Arm / Disarm Interface
- E2E Health Check
- RAID 5

Specifications

MODEL		GN8916	GN8932
CAMERA INTERFACE	CONFIGURATION	Dedicated network / Shared network	
	RESOLUTIONS	4K, WQHD, 1080p, 720p	
	MAX. CHANNELS	16	32
	DEDICATED VIDEO PORTS	1x, 1000base-T	
	COMPATIBLE MODELS	TeleEye MP, MQ & ONVIF (Profile S)	
VIDEO	OUTPUTS	1x HDMI (max. resolution 4K) 1x VGA (max. resolution 1080p)	
CODING	VIDEO & AUDIO	Enhanced H.264, H.264, H.265	
RECORDING	MODES	Manual, Scheduled, Event-driven	
	STORAGE	8x SATA, internal	
	MAX. RECORDING PERFORMANCE	25fps per channel @ 4K 25fps per channel @WQHD 25fps per channel @ 1080p	
	RAID 5	Yes	
EVENT	TYPES	External Alarm, Video Motion Detection, System Tamper, Power Interruption, HDD Failure	
	ACTIONS	Dialback, Buzzer, Email Notification, Relay Control, Telemetry Preset	
	CONTROLS	Arm/Disarm, Security Switch, Power Interruption, Tamper Detection	
	ALARM INPUTS	16x on DVR / Alarm Inputs on Cameras	
	VIDEO MOTION DETECTION	Yes	
	PRE/POST ALARM IMAGE SEQUENCE	Yes	
AUDIO	INPUTS	1x RCA on DVR / Audio Inputs on Cameras	
	OUTPUTS	1x RCA on DVR / Audio Outputs on Cameras	
COMMUNICATION	NETWORK	100/1000 based-T	
	SURELINK	Yes	
	THROUGHPUT CONTROL	Yes	
	WEB SERVER	Built-in	
	JOYSTICK CONTROL	RX-KB07	
	USB	3 x USB 2.0	
POWER	RATING	AC 100-240V, 3.5-2A	
OPERATING ENVIRONMENT	AMBIENT TEMPERATURE	-10°C - 55°C	
	RELATIVE HUMIDITY	10% - 90% (no condensation)	
MECHANICAL DESIGN	DIMENSION	440x95x440mm	
	WEIGHT	7.6kg	

TeleEye Group

Hong Kong China Malaysia
Philippines South Africa Sri Lanka Turkey U.K.

DISTRIBUTED BY: