



- 1/2.8" 1080p Starlight CMOS sensor
- Up to 1000 TVL resolution
- f=2.8mm Fixed Lens
 Angle of view 101°
- 10~20M IR illumination range
- IP66 water proof

AF261 1080p Starlight AHD IR Fixed Bullet



Unit: mm





Terms & Conditions 使用細則 Design and specifications are subject to change without prior notice. Copyright © 2019 Signal Communications Limited. TeleEye is a trademark of Signal Communications Limited and is registered in China, European Community, Hong Kong, U.S. and other countries. All other trademarks are the property of their respective owners.



TeleEye Group Hong Kong China Malaysia Philippines South Africa Sri Lanka United Kingdom FUNCTION

VIDEO

POWER

OPERATING ENVIRONMENT

MECHANICAL

IMAGE SENSOR	1/2.8" 1080p Starlight CMOS
RESOLUTION	1920 x 1080
VIDEO OUTPUT	AHD/TVI/CVI/CVBS (BNC)
FRAME RATE	30fps(60Hz), 25fps(50Hz)
MINIMUM ILLUMINATION	0 Lux / F1.4 (IR ON)
IR LED / IR DISTANCE	10~20M
LENS	f=2.8mm lens
ANGLE OF VIEW	101°
ELECTRONIC SHUTTER	Auto; 1/25s~1/50000s(PAL); 1/30s~1/50000s(NTSC)
S/N RATIO	≥52dB(AGC OFF)
FUNCTION CONTROL	OSD (COC Control)
DAY & NIGHT	ICR
WDR	Yes(120dB)
DIGITAL NR	Yes (3D DNR)
AGC	Yes
AUTO WHITE BALANCE	Yes
BLC	Yes
HLC	Yes
LSC	Yes
SHARPNESS	Yes
BRIGHTNESS	Yes
SMART IR	Yes
POWER SUPPLY	12VDC
POWER CONSUMPTION	IR OFF : < 1.5W; IR ON : < 4W
AMBIENT TEMPERATURE	- 30 °C ~ 50 °C
RELATIVE HUMIDITY	10% - 90%
WATER PROOF	IP66
DIMENSION	70mm x 70mm x 156mm
WEIGHT	320g