

- 1/2.7" 5MP CMOS sensor
- 4MP (2560x1440)@25/30 fps
- 5MP (2592x1944)@20fps
- AHD/TVI/CVI/CVBS video output
- Up to 1500TVL resolution
- f=2.8-12mm Vari-Focal lens
- Angel of view 95.7° ~ 35.9°
- 20~30M IR illumination range
- IP66 weather proof

## AF526



### 5MP AHD IR Vari-Focal Dome



Model

AF526

Unit: mm



#### VIDEO

<b>Image Sensor</b>	1/2.7" 5MP CMOS
<b>Resolution</b>	4MP 2560x1440(Default output) / 5MP 2592x1944
<b>Video Output</b>	AHD/TVI/CVI/CVBS (BNC)
<b>Frame Rate</b>	5MP@20fps / 4MP@25/30fps
<b>Minimum Illumination</b>	0 lux with IR
<b>IR Distance</b>	20~30M
<b>Lens</b>	f=2.8-12mm lens
<b>Angle of view</b>	95.7° ~ 35.9°
<b>Electronic Shutter</b>	Auto / Manual(x30s~1/50000s), FLK
<b>S/N Ratio</b>	≥38dB ( AGC OFF )

#### FUNCTION

<b>Function Control</b>	OSD
<b>Day &amp; Night</b>	AUTO / EXT / B/W / COLOR
<b>Digital WDR</b>	Yes
<b>Digital NR</b>	Yes ( 2D DNR )
<b>AGC</b>	Yes
<b>Auto White Balance</b>	Yes
<b>Mirror Image</b>	Yes
<b>Sharpness</b>	Yes
<b>Brightness</b>	Yes
<b>Lens Shading Compensation</b>	Yes

#### POWER

<b>Power Supply</b>	12VDC
<b>Power Consumption</b>	< 8W

#### OPERATING ENVIRONMENT

<b>Ambient Temperature</b>	- 20°C ~ 55 °C
<b>Relative Humidity</b>	10%-90%

#### MECHANICAL DESIGN

<b>Weather Proof</b>	IP66
<b>Dimension</b>	Φ 132mm x 113mm
<b>Weight</b>	830g

Terms & Conditions 使用細則  
Design and specifications are subject to change without prior notice. Copyright © 2018 Signal Communications Limited. TeleEye is a trademark of Signal Communications Limited and is registered in China, European Community, Hong Kong, U.S. and other countries. All other trademarks are the property of their respective owners.