

GN8932

4K Digital Video Recorder

TeleEye GN8 Series is TeleEye's latest 4K digital video recorders which are capable of recording videos up to 4K resolution which is equivalent to 3840 x 2160 pixels. Events are recorded in ultra-high video quality, providing much more useful information for post-incident investigations.

- 4K (3840 x 2160)
- H.265
- Hacker Resistant
- Pre/Post Alarm Image
- Arm/Disarm Interface
- E2E Health Check
- RAID 5



Model GN8932

Model	GN8932	
CAMERA INTERFACE	CONFIGURATION	Dedicated Network/Shared Network
	RESOLUTIONS	4K, WQHD, 1080p, 720p
	MAX. CHANNELS	32
	DEDICATED VIDEO PORTS	1x, 1000base-T
	COMPATIBLE MODELS	TeleEye MP, MQ & ONVIF (Profile S)
VIDEO	OUTPUTS	1x HDMI (max. resolution 4K), 1x VGA (max. resolution 1080p)
CODING	VIDEO & AUDIO	H.265, Enhanced H.264, H.264
RECORDING	MODES	Manual, Scheduled, Event-driven
	STORAGE	8x SATA, internal
	MAX. RECORDING PERFORMANCE	25fps per channel @ 4K 25fps per channel @ WQHD 25fps per channel @ 1080p
	RAID 5	Yes
EVENT	TYPES	External Alarm, Video Motion Detection, System Tamper, Power Interruption, HDD Failure
	ACTIONS	Dialback, Buzzer, Email Notification, Relay Control, Telemetry Preset
	CONTROLS	Arm/Disarm, Security Switch, Power Interruption, Tamper Detection
	ALARM INPUTS	16x on DVR + Alarm Inputs on Cameras
	VIDEO MOTION DETECTION	Yes
	PRE/POST ALARM IMAGE SEQUENCE	Yes
	RELAY	OUTPUTS
AUDIO	INPUTS	1x RCA on DVR and Audio Inputs on Cameras
	OUTPUTS	1x RCA on DVR and Audio Outputs on Cameras
COMMUNICATION	NETWORK	100/1000 based-T
	SURELINK	Yes
	THROUGHPUT CONTROL	Yes
	WEB SERVER	Built-in
	JOYSTICK CONTROL	RX-KB07
	USB	3 x USB 2.0
POWER	RATING	AC 100-240V, 3.5-2A
OPERATING ENVIRONMENT	AMBIENT TEMPERATURE	-10°C - 55°C
	RELATIVE HUMIDITY	10% - 90% (no condensation)
MECHANICAL DESIGN	DIMENSION	440mm x 95mm x 440mm
	WEIGHT	7.6kg