



# GN9132

## 4K Digital Video Recorder

TeleEye GN9 Series is TeleEye's latest 4K digital video recorders which are capable of recording videos up to 4K resolution which is equivalent to 3840 x 2160 pixels. Events are recorded in ultra-high video quality, providing much more useful information for post-incident investigations.

- 4K (3840 x 2160)
- H.265
- Hacker Resistant
- Pre/Post Alarm Image
- Arm/Disarm Interface
- E2E Health Check
- RAID 5



Model GN9132

|                       |   |                               |                                                                                 |
|-----------------------|---|-------------------------------|---------------------------------------------------------------------------------|
| CAMERA INTERFACE      | [ | CONFIGURATION                 | Dedicated Network/Shared Network                                                |
|                       |   | RESOLUTIONS                   | 4K, WQHD, 1080p, 720p                                                           |
|                       |   | MAX. CHANNELS                 | 32                                                                              |
|                       |   | DEDICATED VIDEO PORTS         | 1x, 1000base-T                                                                  |
| VIDEO                 | - | COMPATIBLE MODELS             | TeleEye MP, MQ, MS & ONVIF (Profile S)                                          |
|                       |   | OUTPUTS                       | 1x HDMI (max. resolution 4K), 1x VGA (max. resolution 1080p)                    |
| CODING                | - | VIDEO & AUDIO                 | H.265, Enhanced H.264, H.264                                                    |
|                       |   | MODES                         | Manual, Scheduled, Event-driven                                                 |
| RECORDING             | [ | STORAGE                       | 8x SATA, internal                                                               |
|                       |   | MAX. RECORDING PERFORMANCE    | 25fps per channel @ 4K<br>25fps per channel @ WQHD<br>25fps per channel @ 1080p |
|                       |   | RAID 5                        | Yes                                                                             |
|                       |   | TYPES                         | External Alarm, Video Motion Detection, HDD Failure                             |
| EVENT                 | [ | ACTIONS                       | Dialback, Buzzer, Email Notification, Relay Control, Telemetry Preset           |
|                       |   | CONTROLS                      | Arm/Disarm, Security Switch                                                     |
|                       |   | ALARM INPUTS                  | 16x on DVR + Alarm Inputs on Cameras                                            |
|                       |   | VIDEO MOTION DETECTION        | Yes                                                                             |
|                       |   | PRE/POST ALARM IMAGE SEQUENCE | Yes                                                                             |
|                       |   | OUTPUTS                       | 8                                                                               |
| AUDIO                 | [ | INPUTS                        | 1x RCA on DVR and Audio Inputs on Cameras                                       |
|                       |   | OUTPUTS                       | 1x RCA on DVR and Audio Outputs on Cameras                                      |
| COMMUNICATION         | [ | NETWORK                       | 100/1000 based-T                                                                |
|                       |   | SURELINK                      | Yes                                                                             |
|                       |   | THROUGHPUT CONTROL            | Yes                                                                             |
|                       |   | WEB SERVER                    | Built-in                                                                        |
|                       |   | USB                           | 1 x USB 3.0, 1 x USB 2.0                                                        |
| POWER                 | - | RATING                        | AC 100-240V, 250W                                                               |
| OPERATING ENVIRONMENT | [ | AMBIENT TEMPERATURE           | -10°C - 55°C                                                                    |
|                       |   | RELATIVE HUMIDITY             | 10% - 90% (no condensation)                                                     |
| MECHANICAL DESIGN     | [ | DIMENSION                     | 440mm x 95mm x 440mm                                                            |
|                       |   | WEIGHT                        | 7.6kg                                                                           |

Terms & Conditions 使用細則  
Design and specifications are subject to change without prior notice. Copyright © 2024 TeleEye Intelligence Limited.  
TeleEye is a trademark of TeleEye Intelligence Limited and is registered in China, European Community, Hong Kong, U.S. and other countries. All other trademarks are the property of their respective owners.