





Features

- 1080p IR Vari-Focal dome
- 1 / 2.7 " 2MP CMOS sensor, 25/30fps
- H.264 / MJPEG compression
- 3 independent video streams
- f=2.8 ~ 12 mm vari-focal lens
- ~25m IR illumination range
- IP66 & IK10 ingress protection
- Power over Ethernet, PoE
- True day & night operation with auto IR-cut filter
- ONVIF Profile S

Dimensions

Unit: mm



Specifications

MODEL		MP2125E-HD
VIDEO	IMAGE SENSOR	1 / 2.7 " 2MP CMOS Sensor
	RESOLUTION	1080P (1920×1080), 720P (1280×720), D1, CIF, 480×240
	FRAME RATE	Up to 25/30fps
	MINIMUM ILLUMINATION	0.05 lux @F1.2,AGC ON; 0 lux with IR ~25m
	LENS	f=2.8 ~ 12 mm
	AUTO IR-CUT FILTER	Yes
	VIDEO SETTINGS	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR
AUDIO	INPUT	1 ch
CONNECTIVITY	NETWORK INTERFACE	RJ-45
	NETWORK PROTOCOL	TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	DYNAMIC IP	sureLINK, DDNS
	VIDEO MAIN STREAM RESOLUTION	1920 x 1080 / 1280 x 720
	VIDEO SUB STREAM 1 RESOLUTION	D1 / CIF
	VIDEO SUB STREAM 2 RESOLUTION	480 x 240 / CIF
	CONCURRENT USERS	4 (Independent)
COMPRESSION	WEB SERVER	Built-in
	VIDEO COMPRESSION	H.264 / MJPEG
	VIDEO STREAMING	3 Independent Streams
POWER	POWER IN	12V DC / PoE
	MAX. RATING	3.5W / 5.5W (IR On)
OPERATING ENVIRONMENT	AMBIENT TEMPERATURE	-20°C - 50°C
	RELATIVE HUMIDITY	10 ~ 90% (No Condensation)
MECHANICAL DESIGN	WEATHER PROOF	IP66
	VANDAL RESISTANT	Yes
	NET WEIGHT	960g

TeleEye Group

Hong Kong Bangladesh China Malaysia
Philippines South Africa Sri Lanka Turkey U.K.

Design and specifications are subject to change without prior notice. Copyright © 2016 Signal Communications Limited.
TeleEye is a trademark of Signal Communications Limited and is registered in China, European Community, Hong Kong, U.S. and other countries. All other trademarks are the property of their respective owners.

DISTRIBUTED BY:

www.TeleEye.com