

TeleEye



- 1/2.8" 2MP Starlight CMOS sensor
- Electric vari-focal
f=2.8mm ~ 12mm lens
Angle of view: 103° ~ 32°
- 30-50m IR illumination range
- H.265 / H.264 compression
- AI Detection:
Face detection
Human / Vehicle detection
- IP67 Water proof
- Power over Ethernet
- ONVIF Profile S

MP2536AE

1080p IR Electric Vari-Focal Dome



Unit: mm



Accessories



Junction Box: JB0302



Wall Mount Bracket:
JB0302 + WM0407



WM0203

Terms & Conditions 使用細則
Design and specifications are subject to change without prior notice. Copyright © 2020 Signal Communications Limited. TeleEye is a trademark of Signal Communications Limited and is registered in China, European Community, Hong Kong, U.S. and other countries. All other trademarks are the property of their respective owners.

Contact Us 聯絡我們
Tel: (+852) 2995 5992 URL: www.TeleEye.com

TeleEye Group
Hong Kong China Malaysia Philippines
South Africa Sri Lanka United Kingdom

MODEL

MP2536AE

VIDEO	IMAGE SENSOR	1/2.8" 2MP Starlight CMOS sensor
	RESOLUTION	1080P (1920×1080), 720P (1280×720), D1, CIF, 480×240
	FRAME RATE	Up to 25/30fps
	MINIMUM ILLUMINATION	0.0038 lux @F1.4, AGC ON; 0 lux with IR
	IR DISTANCE	30 ~ 50M
	LENS	f=2.8 ~ 12mm @F1.4 motorized zoom lens
	ANGLE OF VIEW	103° ~ 32°
AUDIO	ELECTRONIC SHUTTER	1 / 25 s ~ 1 / 100000 s
	VIDEO SETTINGS	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc
CONNECTIVITY	INPUT	1CH Audio input or 1CH Built-in MIC
	NETWORK INTERFACE	RJ45 × 1, 10M / 100M self-adaption
	NETWORK PROTOCOL	TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, 802.1x, UPnP, HTTPs, QoS
	CONCURRENT USERS	10
COMPRESSION	WEB SERVER	Built-in
	ONVIF	Profile S
	VIDEO COMPRESSION	H.265 / H.264
FUNCTIONS	VIDEO STREAMING	3 Independent Streams
	AUDIO COMPRESSION	G711A/U
	AI DETECTION	Face detection; Human detection; Vehicle detection
EDGE RECORDING	SMART ALARM	Intrusion detection; Line crossing detection; Video Exception; Motion detection
	ACTION	Snap, Recording, Email
POWER	MICRO SD Card	Max. 128GB
	VOLTAGE	12VDC
	MAX. RATING	<10.5W
OPERATING ENVIRONMENT	POE	YES
	AMBIENT TEMPERATURE	-30°C ~ 60°C
MECHANICAL DESIGN	RELATIVE HUMIDITY	Less than 95% (non-condensing)
	WATER PROOF	IP67
	DIMENSION	Φ 111.5mm x 100mm
	WEIGHT	670g