



- 1/3" 4MP CMOS sensor
- f=2.8mm fixed lens
Angle of view: 100°
- 10m IR illumination range
- H.265 / H.264 compression
- AI Detection:
Face detection
Human / Vehicle detection
- IP66 & IK10 ingress protection
- Power over Ethernet
- ONVIF Profile S

MP4011AE

4MP Network IR Fixed Dome with AI Detection



Unit: mm



Accessories



Wall Mount Bracket: WM0203

Terms & Conditions 使用細則
Design and specifications are subject to change without prior notice. Copyright © 2020 Signal Communications Limited. TeleEye is a trademark of Signal Communications Limited and is registered in China, European Community, Hong Kong, U.S. and other countries. All other trademarks are the property of their respective owners.

MODEL

MP4011AE

VIDEO	IMAGE SENSOR	1/3" 4MP CMOS
	RESOLUTION	4MP (2560×1440), 3MP (2304×1296), 1080P (1920×1080), 720P (1280×720), D1, CIF, 480×240
	FRAME RATE	Up to 25/30fps
	MINIMUM ILLUMINATION	0.005 lux @F1.6, AGC ON; 0 lux with IR
	IR DISTANCE	10M
	LENS	f=2.8mm @F1.6 fixed lens
	ANGLE OF VIEW	100°
	ELECTRONIC SHUTTER	1 / 30 s ~ 1 / 100000 s
AUDIO	VIDEO SETTINGS	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc
	INPUT	1CH Audio input or 1CH Built-in MIC
CONNECTIVITY	NETWORK INTERFACE	RJ45 × 1, 10M / 100M self-adaption
	NETWORK PROTOCOL	TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP,HTTP, 802.1x, UPnP, HTTPs, QoS
	CONCURRENT USERS	4
	WEB SERVER	Built-in
COMPRESSION	ONVIF	Profile S
	VIDEO COMPRESSION	H.265 / H.264
	VIDEO STREAMING	3 Independent Streams
FUNCTIONS	AUDIO COMPRESSION	G711A/U
	AI DETECTION	Face detection; Human detection; Vehicle detection
	SMART ALARM	Intrusion detection; Line crossing detection; Video Exception; Motion detection
EDGE RECORDING	ACTION	Snap, Recording, Email
	MICRO SD Card	Max. 128GB
POWER	VOLTAGE	12VDC
	MAX. RATING	<7W
	POE	YES, IEEE802.af
OPERATING ENVIRONMENT	AMBIENT TEMPERATURE	-30°C ~ 60°C
	RELATIVE HUMIDITY	Less than 95% (non-condensing)
MECHANICAL DESIGN	WATER PROOF	IP66
	VANDAL RESISTANT	IK10
	DIMENSION	Φ 110 mm x 58mm
	WEIGHT	360g