



- 1/3" 4MP CMOS sensor, 25/30fps
- H.265/ H.264 compression
- 3 independent video streams
- 10m IR illumination range
- f=2.8mm fixed lens
- TF card storage, up to 128GB •
- One built-in microphone
- IP66 & IK 10 ingress protection
- Power over Ethernet
- ONVIF Profile S





Terms & Conditions 使用細則
Design and specifications are subject to char

nge without prior notice. Copyright © 2018 Signal Communications Limited. TeleEye is a trademark of Signal Communications Limited and is registered in China, European Community, Hong Kong, U.S. and other countries. All other trademarks are the property of their respective owners.

TeleEye Group

ng Kong China Malaysia Philippines uth Africa Sri Lanka United Kingdom



MP411AE-HD

WQHD IR Fixed Dome



		Model	MP411AE-HD
	Г	IMAGE SENSOR	1/3" 4MP CMOS Sensor
VIDEO			2560 x 1440 / 2304 x 1296 /
		RESOLUTION	1920 x 1080 (1080p) / 1280 x 720 (720p) /
			D1 / CIF / 480 x 240
		FRAME RATE	Up to 25/30fps
		MINIMUM ILLUMINATION	0.05 lux @F1.2, AGC ON; 0 lux with IR
		IR Distance	0~10m
		LENS	f=2.8mm Fixed Lens
		VIEW ANGLE	100°
		ELECTRONIC SHUTTER	1 / 25 s ~ 1 / 100000 s
		VIDEO SETTINGS	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc.
	L	ANALOG VIDEO OUTPUT	CVBS video output (BNC × 1)
AUDIO	_	INPUT	LINE IN × 1 or one built-in microphone
CONNECTIVITY	Г	NETWORK INTERFACE	RJ45
		NETWORK PROTOCOL	TCP / IP, UDP, DHCP, NTP, RTSP, PPP₀E, DDNS, SMTP, FTP
		CONCURRENT USERS	10
		WEB SERVER	Built-in
	L	ONVIF	Profile S
COMPRESSION	Г	VIDEO COMPRESSION	H.265 / Enhanced H.264
	L	VIDEO STREAMING	3 Independent Streams
EVENT HANDLING	Г	MOTION DETECTION	Yes
	L	ACTION	Snap, Recording, Email
EDGE RECORDING	-	TF Card	Max. 128GB
POWER OPERATING ENVIRONMENT	Г	VOLTAGE	12VDC
		MAX. RATING	3.5W / 4.5W (IR On)
	L	POE	YES
	Г	AMBIENT TEMPERATURE	-20°C ~ 50°C
	L	RELATIVE HUMIDITY	10%-90%
MECHANICAL DESIGN	Г	WEATHER PROOF	IP66
		VANDAL RESISTANT	IK10
		DIMENSION	Φ110mm× 58mm
	L	WEIGHT	360g