

MP6242-HD

40 x Optical Zoom 4MP Network IR Speed Dome

- 1/2.8" 4MP Progressive CMOS Sensor
- Max. Resolution: 2560x1440 @20/30fps
- 40x Optical Zoom
- 350M IR Distance
- H.265 / H.264 Compression
- AI Detection: Human / Vehicle detection
- Auto-tracking
- IP67 & IK10 ingress protection
- TVS 6KV Lightning Protection, Surge Protection




Model

MP6242-HD

Dimension:

Unit: mm



VIDEO

IMAGE SENSOR	1/2.8" 4MP Progressive CMOS
MAX. RESOLUTION	2560x1440
FRAME RATE	Up to 30fps
MINIMUM ILLUMINATION	Color 0.005 Lux @ (F1.2 AGC ON); B/W 0.001Lux @ (F1.2 AGC ON); 0.0Lux, IR ON; ~350M IR distance
LENS	40x Optical zoom, f=4.5mm ~ 180mm, MAX F1.2
VIEW ANGLE	H: 56°~ 1.8° / W: 33°~1.1°
ELECTRONIC SHUTTER	Auto/ Manual (1/25~1/25000s)

AUDIO

INPUT	1CH
OUTPUT	1CH

FUNCTION

PAN RANGE	360° endless rotation
PAN SPEED	Preset speed: 300°/s; Manual control speed: 0.1 ~ 270°/s
TILT RANGE	-25° ~ 155°, auto flip at 90°
TILT SPEED	Tile speed: 300°/s; Manual control speed: 0.1 ~ 270°/s
PRESET	360
CRUISE	8
TRACK	4
SCHEDULE TASK	Preset/Cruise/Trace/Scan/Dome reboot
SCAN	1
HOME POSITION	Yes

CONNECTIVITY

NETWORK INTERFACE	RJ-45
NETWORK PROTOCOL	HTTP, HTTPS, IPv4/IPv6, 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE
WEB SERVER	Built-in
ONVIF	Profile S

COMPRESSION

VIDEO COMPRESSION	H.265 / Enhanced H.264
VIDEO STREAMING	3

EVENT HANDLING

ALARM INPUT	1 (Dry contact)
ALARM OUTPUT	1

EDGE RECORDING

TF CARD	Max. 256GB
---------	------------

POWER

POE	PoE+ (802.3.at, Type 2)
POWER SUPPLY	DC24V / 2500mA
MAX. RATING	23 W(IR on)

OPERATING ENVIRONMENT

AMBIENT TEMPERATURE	-40°C ~ 670°C
RELATIVE HUMIDITY	≤ 95%

Terms & Conditions 使用細則

Design and specifications are subject to change without prior notice. Copyright © 2023 Signal Communications Limited. TeleEye is a trademark of Signal Communications Limited and is registered in China, European Community, Hong Kong, US, and other countries. All other trademarks are the property of their respective owners.



MP6242-HD

40 x Optical Zoom 4MP Network IR Speed Dome

Accessories:



Pole mount PTC-MQ61PD



Pendant mount PTC-MQ61PL



Corner mount PTC-MQ61CN

MECHANICAL DESIGN

WEATHER PROOF	IP67
VANDAL RESISTANT	IK10
PROTECTION LEVEL	TVS 6KV lightning protection, surge protection
DIMENSION	197 x 302 mm
WEIGHT	3.0Kg

SMART FEATURES

AI DETECTION	Human detection; Vehicle detection
SMART ALARM	Intrusion detection, Line crossing detection; Video Exception; Motion detection
SMART TRACKING	Support Smart tracking of human or vehicle
ACTION	Snap, Recording , Alarm output, Email

----- END -----

Terms & Conditions 使用細則

Design and specifications are subject to change without prior notice. Copyright © 2023 Signal Communications Limited. TeleEye is a trademark of Signal Communications Limited and is registered in China, European Community, Hong Kong, US, and other countries. All other trademarks are the property of their respective owners.



TeleEye Group
Hong Kong China Malaysia Philippines
South Africa Sri Lanka United Kingdom