




Features

- 1080p HD IR Vari-Focal dome
- 1/2.8" SONY CMOS sensor, 30fps
- H.264 compression
- 2 independent video streams
- f=2.8mm ~ 12mm vari-focal lens
- ~20m IR illumination range
- IP66 weather proof
- Vandal resistance
- Power over Ethernet, PoE
- ONVIF Profile S

Dimension

Unit: mm



Specifications

MODEL		MQ225E-HD
VIDEO	IMAGE SENSOR	1/2.8" SONY CMOS Sensor
	RESOLUTION	1920 x 1080 (1080p)
	FRAME RATE	Up to 30fps
	MINIMUM ILLUMINATION	0.0 Lux, IR ON, ~20m
	LENS	f=2.8mm ~ 12mm
	VIEW ANGLE	31-95 degree
	ELECTRONIC SHUTTER	Auto / Manual
	VIDEO SETTINGS	Brightness / Contrast / Saturation / Mirroring / Exposure / White Balance / Flickerless Control / Sharpness / WDR / Noise Reduction
AUDIO	INPUT	1CH
	OUTPUT	1CH
CONNECTIVITY	NETWORK INTERFACE	RJ-45
	CONCURRENT USERS	4
	WEB SERVER	Built-in
	ONVIF	Profile S
COMPRESSION	VIDEO COMPRESSION	H.264, JPEG
	VIDEO STREAMING	Dual Stream
EVENT HANDLING	PRIVACY ZONE	4
	SNAP SHOT	JPEG
	MOTION DETECTION	Yes
	ACTION	Recording, Alarm Output, Emails snapshot
	ALARM INPUT	2
	RELAY SWITCH	1
EDGE RECORDING	ON-BOARD STORAGE	Max 64GB MicroSD
POWER	POWER IN	12V DC / PoE
	MAX. RATING	9W
OPERATING ENVIRONMENT	AMBIENT TEMPERATURE	-20°C - 55°C
	RELATIVE HUMIDITY	0 ~ 90%
MECHANICAL DESIGN	WEATHER PROOF	IP66
	VANDAL RESISTANT	Yes
	DIMENSIONS	112 x 132mm
	NET WEIGHT	1120g

TeleEye Group

Hong Kong Bangladesh China Malaysia
Philippines South Africa Sri Lanka Turkey U.K.

DISTRIBUTED BY: