

TeleEye



- 1080p IR Dome
- 1/2" Sony 2MP Starlight CMOS sensor
- Electric Vari-focal f=3.6mm ~ 10mm
- Face Recognition
- H.265/Enhanced H.264 compression
- IP66 Water proof
- Vandal resistant
- Power over Ethernet
- ONVIF Profile S

MS1000F

2MP Face Recognition Dome Camera



Unit: mm



Accessories

Junction Box: MQ-JBP06D



Wall Mount Bracket: MQ-WLJ38B



Terms & Conditions 使用細則
Design and specifications are subject to change without prior notice. Copyright © 2019 Signal Communications Limited. TeleEye is a trademark of Signal Communications Limited and is registered in China, European Community, Hong Kong, U.S. and other countries. All other trademarks are the property of their respective owners.

MODEL

MS1000F

VIDEO	IMAGE SENSOR	1/2" Sony 2MP Starlight CMOS
	MAX. RESOLUTION	1920 x 1080
	FRAME RATE	Up to 30fps
	MINIMUM ILLUMINATION	Color: 0.02Lux / F1.4, B/W:0.002Lux / F1.4
	LENS	f=3.6mm ~ 10mm motorized lens (auto / manual focus)
	ANGLE OF VIEW	104° ~ 46°
	ELECTRONIC SHUTTER	1/5~1/100000
CONNECTIVITY	VIDEO SETTINGS	Brightness / Contrast / Saturation / Mirror / Exposure / Sharpness / WDR / 3DNR
	ANALOG VIDEO OUTPUT	1CH 1.0Vp-p composite video output
	NETWORK INTERFACE	RJ-45
COMPRESSION	NETWORK PROTOCOL	TCP/IP,UDP, HTTP, DHCP, RTSP, DDNS, NTP, PPPoE,UPnP, SMTP, FTP
	CONCURRENT USERS	4
	WEB SERVER	Built-in
FACE RECOGNITION	ONVIF	Profile S
	VIDEO COMPRESSION	H.265 / Enhanced H.264
	VIDEO STREAMING	3 Independent Streams
	FACE DETECTION	Sync detection ≤ 10pcs faces targets
	RECOGNITION FACE SIZE	Face pixel ≥150 pixels
	FACE CAPACITY	Support built-in ≤ 3000 faces
	POSTURE	Capture within 25 degrees in vertical, within 60 degrees in horizontal
EVENT	CAPTURE RATE	Capture rate≥98% (meet the above conditions) ; comparison rate≥95%
	COMPARISON RATE	comparison rate≥95%
	RESPONSE SPEED	≤200ms
	RECOGNITION AREA	Full image recognition, support zone optional setting
EDGE RECORDING	MOTION DETECTION	Yes
	ACTION	Recording, Alarm output, Email, Snapshot
	ALARM INPUT	2
POWER	RELAY SWITCH	2
	TF Card	Max. 128GB
OPERATING ENVIRONMENT	EVENT HANDLING	12 VDC
	MAX. RATING	5W
	POE	YES
MECHANICAL DESIGN	AMBIENT TEMPERATURE	-20°C ~ 55°C
	RELATIVE HUMIDITY	0% - 90%
	WATER PROOF	IP66
	VANDAL RESISTANT	IK10
	DIMENSION	117mm x 86mm
	WEIGHT	650g

TeleEye

TeleEye Group
Hong Kong China Malaysia Philippines
South Africa Sri Lanka United Kingdom