

- 4K (3840 x 2160)
- H.265, Enhanced H.264
- Hacker Resistant
- PoE Support
- Pre / Post Alarm Image
- Arm / Disarm Interface
- E2E Health Check
- Duplicated Recording

## Unit: mm

| 132.80  | ~     |         |
|---------|-------|---------|
| - AR 00 | *: [] | TeleEye |
|         |       |         |

## 4K Digital Video Recorder

WS9080



WS9080

MODEL

| MODEL               |   |                               | W 39000  |
|---------------------|---|-------------------------------|--|
|                     | г | CONFIGURATION                 | Dedicated Network/Shared Network   |
|                     |   | RESOLUTIONS                   | 4K, WQHD, 1080p, 720p  |
| CAMERA<br>INTERFACE |   | MAX. CHANNELS                 | 16   |
|                     |   | DEDICATED VIDEO PORTS         | 16x, 100base-T, PoE  |
|                     | L | COMPATIBLE MODELS             | TeleEye MS, MP, MP, MQ & ONVIF (Profile S)   |
| VIDEO               | - | OUTPUTS                       | 1x HDMI (max. resolution 4K)<br>1x VGA (max. resolution 1080p)   |
| CODING              | _ | VIDEO & AUDIO                 | Enhanced H.264, H.264, H.265   |
|                     | Г | MODES                         | Manual, Scheduled, Event-driven  |
|                     |   | STORAGE                       | 8x SATA, internal  |
| RECORDING           |   | MAX. RECORDING<br>PERFORMANCE | 25fps per channel @ 4K<br>25fps per channel @WQHD  |
|                     | L | RAID5                         | Yes  |
|                     | ſ | TYPES                         | External Alarm, Video Motion Detection, System Tamper,<br>Power Interruption, HDD Failure, Object Detection, Face<br>Detection |
| EVENT               |   | ACTIONS                       | Dialback, Buzzer, Email Notification, Relay Control,<br>Telemetry Preset   |
|                     |   | CONTROLS                      | Arm/Disarm, Security Switch, Power Interruption, Tamper Detection  |
|                     | L | ALARM INPUTS                  | 4x on DVR / Alarm Inputs on Cameras  |
| RELAY               | _ | OUTPUTS                       | 1  |
| AUDIO               | Г | INPUTS                        | 1x RCA on DVR / Audio Inputs on Cameras  |
| AUDIO               | L | OUTPUTS                       | 1x RCA on DVR / Audio Outputs on Cameras   |
|                     | Г | NETWORK                       | 100/1000 based-T   |
|                     |   | SURELINK                      | Yes  |
|                     |   | THROUGHPUT CONTROL            | Yes  |
| COMMUNICATION       |   | WEB SERVER                    | Built-in   |
|                     |   | RTSP SERVER                   | Yes  |
|                     |   | JOYSTICK CONTROL              | RX-KB05 / RX-KB07  |
|                     | L | USB                           | 3 x USB 2.0 (1 Front, 2 Rear)  |
| POWER               | - | RATING                        | AC 100-240V, 3.5-2A  |
| OPERATING           | Г | AMBIENT TEMPERATURE           | -10°C ~ 55°C   |
| ENVIRONMENT         | L | RELATIVE HUMIDITY             | 10% - 90% (no condensation)  |
| MECHANICAL          | Г | DIMENSION                     | 440mm x 440mm x 95mm   |
| DESIGN              | L | WEIGHT                        | 7.6kg  |

Contact Us 聯絡我們 Tel: (+852) 2995 5992 URL: www.TeleEye.com

Design and specifications are subject to change without prior notice. Copyright © 2020 Signal Communications Limited. TeleEye is a trademark of Signal Communications Limited and is

registered in China, European Community, Hong Kong, U.S. and other countries. All other trademarks are the property of their respective owners.

TeleEye Group

Hong Kong China Malaysia Philippines South Africa Sri Lanka United Kingdom



Terms & Conditions 使用細則