



Features

- 4K (3840 x 2160)
- H.265
- Hacker Resistant
- Pre / Post Alarm Image
- Arm / Disarm Interface
- E2E Health Check
- Duplicated Recording

Specifications

| MODEL | | WS9540 |
|-----------------------|----------------------------|--|
| CAMERA INTERFACE | CONFIGURATION | Dedicated Network/Shared Network |
| | RESOLUTIONS | 4K, WQHD, 1080p, 720p |
| | MAX. CHANNELS | 8 |
| | DEDICATED VIDEO PORTS | 8x, 100base-T, PoE |
| | COMPATIBLE MODELS | TeleEye MP, MQ & ONVIF (Profile S) |
| VIDEO | OUTPUTS | 1x HDMI (max. resolution 4K) |
| CODING | VIDEO & AUDIO | H.265, Enhanced H.264, H.264 |
| RECORDING | MODES | Manual, Scheduled, Event-driven |
| | STORAGE | 2x SATA, internal |
| | MAX. RECORDING PERFORMANCE | 25fps per channel @ 4K |
| | DUPLICATED RECORDING | Yes |
| EVENT | TYPES | External Alarm, Video Motion Detection, HDD Failure, Object Detection, Face Detection |
| | ACTIONS | Dialback, Buzzer, Email Notification, Mobile Notification, Relay Control, Telemetry Preset |
| | CONTROLS | Arm/DisArm |
| | ALARM INPUTS | Alarm Inputs on Cameras |
| AUDIO | INPUTS | 1x 3.5mm on NVR or Audio Inputs on Cameras |
| | OUTPUTS | 1x 3.5mm on NVR or Audio Outputs on Cameras |
| COMMUNICATION | NETWORK | 100/1000 based-T |
| | SURELINK | Yes |
| | THROUGHPUT CONTROL | Yes |
| | WEB SERVER | Built-in |
| | RTSP SERVER | Yes |
| | USB | 1 x USB 3.0, 1 x USB 2.0 |
| | RATING | DC 12V, 4A |
| POWER | AMBIENT TEMPERATURE | -10°C - 55°C |
| OPERATING ENVIRONMENT | RELATIVE HUMIDITY | 10% - 90% (no condensation) |
| MECHANICAL DESIGN | DIMENSION | 360mm x 242mm x 48mm |
| | WEIGHT | 2.0kg |