



- 1/2.8" 2MP Starlight CMOS sensor
- Up to 1000TVL resolution
- f=2.8mm Fixed Lens
Angle of view 101°
- 10~20M IR illumination range
- IP66 water proof



MODEL

AF231

Unit: mm



VIDEO

IMAGE SENSOR	1/2.8" 2MP Starlight CMOS
RESOLUTION	1920 x 1080
VIDEO OUTPUT	AHD/TVI/CVI/CVBS (BNC)
FRAME RATE	30fps(60Hz), 25fps(50Hz)
MINIMUM ILLUMINATION	0Lux (IR ON); Color: 0.005Lux / F1.2, AGC ON
IR LED / IR DISTANCE	10~20M
LENS	f=2.8mm lens
ANGLE OF VIEW	101°
ELECTRONIC SHUTTER	Auto; 1/25s~1/50000s(PAL); 1/30s~1/50000s(NTSC)
S/N RATIO	≥52dB (AGC OFF)

FUNCTION

FUNCTION CONTROL	OSD (COC Control)
DAY & NIGHT	ICR
WDR	Yes(120dB)
DIGITAL NR	Yes (3D DNR)
AGC	Yes
AUTO WHITE BALANCE	Yes
BLC	Yes
HLC	Yes
LSC	Yes
SHARPNESS	Yes
BRIGHTNESS	Yes
SMART IR	Yes

POWER

POWER SUPPLY	12VDC
POWER CONSUMPTION	IR OFF : < 1.5W; IR ON : < 3W

OPERATING ENVIRONMENT

AMBIENT TEMPERATURE	- 30 °C ~ 50 °C
RELATIVE HUMIDITY	10% - 90%

MECHANICAL DESIGN

WATER PROOF	IP66
DIMENSION	Φ 108mm x 92mm
WEIGHT	360g

Terms & Conditions 使用細則

Design and specifications are subject to change without prior notice. Copyright © 2019 Signal Communications Limited. TeleEye is a trademark of Signal Communications Limited and is registered in China, European Community, Hong Kong, U.S. and other countries. All other trademarks are the property of their respective owners.